

OzCrop Pty Ltd

Chemwatch: 5322-70 Version No: 3.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 3

Issue Date: 01/11/2019 Print Date: 29/01/2020 S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	OzCrop 2,4-D IPA 300 Herbicide
Synonyms	APVMA Code: 66332
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,4-dichlorophenoxyacetic acid isopropylamine salt)
Other means of identification	Not Available
Relevant identified uses of the	substance or mixture and uses advised against

Relevant identified uses Agricultural herbicide.

Details of the supplier of the safety data sheet

Registered company name	OzCrop Pty Ltd
Address	G13/25 Solent Circuit Norwest NSW 2153 Australia
Telephone	(02) 8123 0170
Fax	(02) 8123 0171
Website	http://www.ozcrop.com.au
Email	orders@ozcrop.com.au

Emergency telephone number

<u> </u>	
Association / Organisation	In Transport Emergency DIAL 000
Emergency telephone numbers	1800 033 111 (24 hours - Australia wide)
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	56	
Classification ^[1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Carcinogenicity Category 2, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Chronic Aquatic Hazard Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements



SIGNAL WORD DANGER Hazard statement(s) H302 Harmful if swallowed. H315 Causes skin irritation H318 Causes serious eye damage. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P261	Avoid breathing mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment (see advice on this label).
P362	Take off contaminated clothing and wash before reuse.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P330	Rinse mouth.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
5742-17-6	10-30	2.4-dichlorophenoxyacetic acid isopropylamine salt
Not Available		(300g/l)
Not Available	balance	Ingredients determined not to be hazardous

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.

If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Following exposures to chlorophenoxy compounds:

- Acute toxic reactions are rare. The by-product of production, dioxin, may be implicated in subacute features such as hepatic enlargement, chloracne, neuromuscular symptoms and deranged porphyrin metabolism.
- Large intentional overdoses result in coma, metabolic acidosis, myalgias, muscle weakness, elevated serum creatine kinase, myoglobinuria, irritation of the skin, eyes, respiratory tract and gut and mild renal and hepatic dysfunction.
- Several cases of sensorimotor peripheral neuropathies have been associated with chronic dermal exposure to 2,4-D. For acute exposures the usual methods of gut and skin contamination (lavage, charcoal, cathartic) are recommended in the first several hours. Alkalisation of the urine and generous fluid replacement have the added benefit of treating any myoglobinuria present. Monitor metabolic acidosis, hyperthermia, hyperkalaemia, myoglobinuria and hepatic/renal dysfunction. for 2,4-dichlorophenoxyacetic acid (2,4-D) and its derivatives
- Gastric lavage if there are no signs of impending convulsions.
- Cautious administration of short-acting anticonvulsant drug if convulsions appear imminent.
- General supportive measures for central nervous system depression
- If hypotension appears, search vigorously for a contributing cause (e.g. dehydration, electrolyte balance, acidosis, myocardial disturbances and hyperpyrexia).
- As appropriate, treat dehydration, electrolyte disturbances, acidosis, and hyperexia.
- To promote excretion of 2,4-D, initiate alkaline diuresis, as in salicylate poisoning by injecting sodium bicarbonate, intravenously, until the urine pH exceeds 7.5 and then infuse mannitol; renal clearance rises sharply as urine pH rises above 7.5 above pH 8.0, it is said to be 100-fold greater than pH 6.0.
- F If cardiac disturbances are suspected, monitor ECG continuously when possible. Prepare to deliver defibrillating shocks in the event of ventricular fibrillation.
- F If hypotension intensifies, a trial with a vasopressor drug may be appropriate. Adrenalin (epinephrine) should be avoided because of possible fibrillation.
- If myotonia appears, a trial with quinidine may be helpful.
- Physiotherapy may be necessary for motion disorders associated with peripheral neuritis, myopathy or brain stem dysfunction.
- GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, 5th Ed.

In general, chlorophenoxy herbicides are rapidly absorbed from the gastrointestinal tract and evenly distributed throughout the body; accumulation in human tissues is not expected A steady-state level in the human body will be achieved within 3–5 days of exposure. The herbicides are eliminated mainly in the urine, mostly unchanged, although fenoprop may be conjugated to a significant extent Biological half-lives of chlorophenoxy herbicides in mammals range from 10 to 33 h; between 75% and 95% of the ingested amount is excreted within 96 h. Dogs appear to retain chlorophenoxy acids longer than other species as a result of relatively poor urinary clearance and thus may be more susceptible to their toxic effects. Metabolic conversions occur only at high doses. The salt and ester forms are rapidly hydrolysed and follow the same pharmacokinetic pathways as the free acids

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances. In such an event consider:

- foam.
- dry chemical powder.
- carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). May emit acrid smoke. Decomposes on heating and produces toxic fumes of: carbon dioxide (CO2) hydrogen chloride phosgene nitrogen oxides (NOx) other pyrolysis products typical of burning organic material.
HAZCHEM	•3Z

SECTION 6 ACCIDENTAL RELEASE MEASURES

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Environmental hazard - contain spillage. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Avoid reaction with oxidising agents Avoid strong acids, bases.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIM INGREDIENT DATA Not Available EMERGENCY LIMITS	ITS (OEL)				
Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3	
OzCrop 2,4-D IPA 300 Herbicide	Not Available	Not Available	Not Available	Not Available	
Ingredient	Original IDLH		Revised IDLH		
2,4-dichlorophenoxyacetic acid isopropylamine salt	Not Available		Not Available		
OCCUPATIONAL EXPOSURE BANDING					
Ingredient	Occupational Exposure Band Ratin	g	Occupational Exposure Band Lin	nit	
2,4-dichlorophenoxyacetic acid isopropylamine salt	E		≤ 0.01 mg/m³		

highly effective in protecting workers and will typically be i "he basic types of engineering controls are: Process controls which involve changing the way a job activit Enclosure and/or isolation of emission source which keeps a adds" and "removes" air in the work environment. Ventilation rentilation system must match the particular process and che imployers may need to use multiple types of controls to prev- local exhaust ventilation usually required. If risk of overexpose rotection. Supplied-air type respirator may be required in sp an approved self contained breathing apparatus (SCBA) may Provide adequate ventilation in warehouse or closed storage	a barrier between the worker and the hazard. Well-designed independent of worker interactions to provide this high level ty or process is done to reduce the risk. selected hazard "physically" away from the worker and vent in can remove or dilute an air contaminant if designed proper emical or contaminant in use. went employee overexposure. sure exists, wear approved respirator. Correct fit is essential becial circumstances. Correct fit is essential to ensure adeque y be required in some situations. area. Air contaminants generated in the workplace possess i fresh circulating air required to effectively remove the contaminant in still air).	of protection. tilation that strategically ly. The design of a l to obtain adequate ate protection. s varying "escape"
e highly effective in protecting workers and will typically be i "he basic types of engineering controls are: Process controls which involve changing the way a job activit inclosure and/or isolation of emission source which keeps a adds" and "removes" air in the work environment. Ventilation rentilation system must match the particular process and che imployers may need to use multiple types of controls to prev- local exhaust ventilation usually required. If risk of overexpose rotection. Supplied-air type respirator may be required in sp approved self contained breathing apparatus (SCBA) may Provide adequate ventilation in warehouse or closed storage elocities which, in turn, determine the "capture velocities" of Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in aerosols, fumes from pouring operations, intermittent conta drift, plating acid fumes, pickling (released at low velocity ir direct spray, spray painting in shallow booths, drum filling, of generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel ger very high rapid air motion). Within each range the appropriate value depends on:	independent of worker interactions to provide this high level ty or process is done to reduce the risk. selected hazard "physically" away from the worker and vent n can remove or dilute an air contaminant if designed proper emical or contaminant in use. vent employee overexposure. sure exists, wear approved respirator. Correct fit is essential becial circumstances. Correct fit is essential to ensure adequ y be required in some situations. area. Air contaminants generated in the workplace possess i fresh circulating air required to effectively remove the conta- n still air). ainer filling, low speed conveyer transfers, welding, spray nto zone of active generation) conveyer loading, crusher dusts, gas discharge (active	of protection. tilation that strategically ty. The design of a to obtain adequate ate protection. svarying "escape" minant. Air Speed: 0.25-0.5 m/s (50-100 f/min.) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.)
solvent, vapours, degreasing etc., evaporating from tank (ir aerosols, fumes from pouring operations, intermittent conta drift, plating acid fumes, pickling (released at low velocity ir direct spray, spray painting in shallow booths, drum filling, of generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel gen very high rapid air motion). Vithin each range the appropriate value depends on:	ainer filling, low speed conveyer transfers, welding, spray nto zone of active generation) conveyer loading, crusher dusts, gas discharge (active	0.25-0.5 m/s (50-100 f/min.) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.)
aerosols, fumes from pouring operations, intermittent conta drift, plating acid fumes, pickling (released at low velocity ir direct spray, spray painting in shallow booths, drum filling, of generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel ger very high rapid air motion). Vithin each range the appropriate value depends on:	ainer filling, low speed conveyer transfers, welding, spray nto zone of active generation) conveyer loading, crusher dusts, gas discharge (active	(50-100 f/min.) 0.5-1 m/s (100-200 f/min.) 1-2.5 m/s (200-500 f/min.)
drift, plating acid fumes, pickling (released at low velocity ir direct spray, spray painting in shallow booths, drum filling, o generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel ger very high rapid air motion). Vithin each range the appropriate value depends on:	nto zone of active generation) conveyer loading, crusher dusts, gas discharge (active	f/min.) 1-2.5 m/s (200-500 f/min.)
generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel ger very high rapid air motion). Vithin each range the appropriate value depends on:		f/min.)
very high rapid air motion). Vithin each range the appropriate value depends on:	nerated dusts (released at high initial velocity into zone of	2.5-10 m/s
		(500-2000 f/min.)
Lower end of the range	Upper end of the range	
1: Poom air aurrante minimal ar favourable to conture		
 Room air currents minimal or favourable to capture Contaminants of low toxicity or of nuisance value only. 	1: Disturbing room air currents	
3: Intermittent, low production.	2: Contaminants of high toxicity 3: High production, heavy use	
4: Large hood or large air mass in motion	4: Small hood-local control only	
roducing performance deficits within the extraction apparatu nore when extraction systems are installed or used.	us, make it essential that theoretical air velocities are multipli	ed by factors of 10 or
the wearing of lenses or restrictions on use, should be cr and adsorption for the class of chemicals in use and an a their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should	reated for each workplace or task. This should include a revi account of injury experience. Medical and first-aid personnel available. In the event of chemical exposure, begin eye irriga d be removed at the first signs of eye redness or irritation - le	ew of lens absorption should be trained in tion immediately and ens should be removed
See Hand protection below		
 equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and way the selection of suitable gloves does not only depend on the nanufacturer. Where the chemical is a preparation of several and has therefore to be checked prior to the application. The exact break through time for substances has to be obtain naking a final choice. Personal hygiene is a key element of effective hand care. Glovashed and dried thoroughly. Application of a non-perfumed suitability and durability of glove type is dependent on usage frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN Select gloves tested to a select and the select gloves tested to a select glove to a select glove to a select glove to a select glove table to a select glove the select glove to a select glove to a select glove the select glove to a select glove to a select glove the select glove to a select glove the select glove to a select glove to a select glove the select glove to a select glove to a select glove to a select glove the select glove to a select gl	atch-bands should be removed and destroyed. material, but also on further marks of quality which vary from al substances, the resistance of the glove material can not be ned from the manufacturer of the protective gloves and has to oves must only be worn on clean hands. After using gloves, moisturiser is recommended. . Important factors in the selection of gloves include: 374, US F739, AS/NZS 2161.1 or national equivalent).	m manufacturer to e calculated in advance to be observed when hands should be
According to the second	 bre when extraction systems are installed or used. Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact the wearing of lenses or restrictions on use, should be cally a remove contact lens as of chemicals in use and an a their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should a clean environment only after workers have washed ha national equivalent] Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber DTE: The material may produce skin sensitisation in predispose equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and we eselection of suitable gloves does not only depend on the anufacturer. Where the chemical is a preparation of severa d has therefore to be checked prior to the application. e exact break through time for substances has to be obtai aking a final choice. ersonal hygiene is a key element of effective hand care. Glashed and dried thoroughly. Application of a on-perfumed uitability and durability of glove type is dependent on usage frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity 	 Safety glasses with side shields. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a revia and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel their removal and suitable equipment should be created for each workplace or task. This should include a revia and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irriga remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lea a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 55 national equivalent] We Hand protection below Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber DTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. te selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary fro anufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be d has therefore to be checked prior to the application. te exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has aking a final choice. transmal produce sing a preparation of a non-perfumed moisturiser is recommended. titability and durability of glove type is

according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. • Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for

	 long-term use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: Excellent when breakthrough time > 480 min Good when breakthrough time > 20 min Fair when breakthrough time < 20 min Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task. Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	 Overalls. P.V.C. apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: **"Forsberg Clothing Performance Index".** The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

OzCrop 2,4-D IPA 300 Herbicide

Material	CPI
BUTYL	A
NEOPRENE	A
VITON	А
NATURAL RUBBER	С
PVA	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1	-
up to 50	1000	-	A-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	A-2
up to 100	10000	-	A-3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

 Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear yellow to brown coloured liquid with mild ammoniacal o	dour; mixes with water.	
Physical state	Liquid	Relative density (Water = 1)	~1.1 @25C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	~0	Viscosity (cSt)	Not Available

Initial boiling point and boiling range (°C)	~100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	*2.37 @20C (water)	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

-			
Inhaled	The material can cause respiratory irritation in some p	erated by the material during the course of normal handling, may be harmful. bersons. The body's response to such irritation can cause further lung damage. in sore throat, burning sensations in the throat and chest, cough, tears, inflamed nose, n from the lungs.	
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Chlorphenoxy compounds irritate the digestive system and cause nausea and vomiting, chest pain, and diarrhoea. Taking large doses can result in mineral imbalance, temperature changes, hyperventilation, low blood pressure, dilated blood vessels, damage to the heart and liver with death of white blood cells, and convulsions.		
Skin Contact	loss of sensation.	ititis condition bosed to this material the skin of humans. Severe peripheral neuropathy has followed causing limb paralysis and is, abrasions or lesions, may produce systemic injury with harmful effects. Examine the ski	
Eye	If applied to the eyes, this material causes severe eye	e damage. Corneal injury resulting from 2,4-D exposure may be slow to heal.	
Chronic	Long-term exposure to respiratory irritants may result Skin contact with the material is more likely to cause a Substance accumulation, in the human body, may occ	cancer or mutations, but there is not enough data to make an assessment. in airways disease, involving difficulty breathing and related whole-body problems. a sensitisation reaction in some persons compared to the general population. cur and may cause some concern following repeated or long-term occupational exposure. cancers of soft tissue, lymph and bronchi. Inflammation of skin can result from long term	
OzCrop 2,4-D IPA 300	ΤΟΧΙΟΙΤΥ	IRRITATION	
Herbicide	Not Available	Not Available	
2.4-dichlorophenoxyacetic	ΤΟΧΙΟΙΤΥ	IRRITATION	
2,4-dichlorophenoxyacetic acid isopropylamine salt	Not Available	Not Available	
acid isopropylamine sait			
Legend:	 Value obtained from Europe ECHA Registered Sub specified data extracted from RTECS - Register of To 	ostances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise xic Effect of chemical Substances	

known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack

Continued...

	rates related to the concentration of and dura that occurs as a result of exposure due to hig exposure ceases. The disorder is characteriz No significant acute toxicological data identifi For chlorophenoxy pesticides: 551chlph WARNING: This substance has been classifi Side-reactions during manufacture of the par	ation of exposure to the irritating substance. (gh concentrations of irritating substance (ofte zed by difficulty breathing, cough and mucus fied in literature search. fied by the IARC as Group 2B: Possibly Carci rent compound may result in the production of	inogenic to Humans. f trace amounts of polyhalogenated aromatic
	hydrocarbon(s). Halogenated phenols, and e Polyhalogenated aromatic hydrocarbons (PH		
	Polyhalogenated aromatic hydrocarbons (PH eyelid swellings and visual disturbances may	HAHs) can cause effects on hormones and m y occur.	imic thyroid hormone. Acne, discharge in the eye,
Acute Toxicity	Polyhalogenated aromatic hydrocarbons (PH	HAHs) can cause effects on hormones and m	
Acute Toxicity Skin Irritation/Corrosion	Polyhalogenated aromatic hydrocarbons (PH eyelid swellings and visual disturbances may	HAHs) can cause effects on hormones and m y occur.	imic thyroid hormone. Acne, discharge in the eye,
Skin Irritation/Corrosion	Polyhalogenated aromatic hydrocarbons (PH eyelid swellings and visual disturbances may	HAHs) can cause effects on hormones and m y occur. Carcinogenicity	imic thyroid hormone. Acne, discharge in the eye,
	Polyhalogenated aromatic hydrocarbons (PH eyelid swellings and visual disturbances may	HAHs) can cause effects on hormones and m y occur. Carcinogenicity Reproductivity	imic thyroid hormone. Acne, discharge in the eye,

— Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

OzCrop 2,4-D IPA 300	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Herbicide	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
2,4-dichlorophenoxyacetic acid isopropylamine salt	LC50	96	Fish	237mg/L	4
	EC50	48	Crustacea	583mg/L	4
Legend:		1. IUCLID Toxicity Data 2. Europe ECHA Registered			
	(/	'3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data			

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil Persistence: Air		
	No Data available for all ingredients No Data available for all ingredients		
Bioaccumulative potential			
Ingredient	Bioaccumulation		
	No Data available for all ingredients		
Mobility in soil			
Ingredient	Mobility		
	No Data available for all ingredients		

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods	
Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Recycle containers if possible, or dispose of in an authorised landfill.

Labels	Reg	wire	h
Labela	Ney	uneu	-

Marine Pollutant		
HAZCHEM	•3Z	

Land transport (ADG)

UN number	3082		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,4-dichlorophenoxyacetic acid isopropylamine salt)		
Transport hazard class(es)	Class 9 Subrisk Not Applicable		
Packing group	III		
Environmental hazard	Environmentally hazardous		
Special precautions for user	Special provisions274 331 335 375 AU01Limited quantity5 L		

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in;

(a) packagings;

(b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L). - Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

UN number	3082			
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. * (contains 2,4-dichlorophenoxyacetic acid isopropylamine salt)			
	ICAO/IATA Class	9		
Transport hazard class(es)	ICAO / IATA Subrisk	isk Not Applicable		
	ERG Code	9L		
Packing group	11			
Environmental hazard	Environmentally hazardous			
Special precautions for user	Special provisions		A97 A158 A197	
	Cargo Only Packing Instructions		964	
	Cargo Only Maximum Qty / Pack		450 L	
	Passenger and Cargo Packing Instructions		964	
	Passenger and Cargo Maximum Qty / Pack		450 L	
	Passenger and Cargo Limited Quantity Packing Instructions		Y964	
	Passenger and Cargo Limited Maximum Qty / Pack		30 kg G	

Sea transport (IMDG-Code / GGVSee)

UN number	3082		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2,4-dichlorophenoxyacetic acid isopropylamine salt)		
Transport hazard class(es)	IMDG Class 9 IMDG Subrisk Not Applicable		
Packing group	III		
Environmental hazard	Marine Pollutant		
Special precautions for user	EMS NumberF-A , S-FSpecial provisions274 335 969Limited Quantities5 L		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

2,4-DICHLOROPHENOXYACETIC ACID ISOPROPYLAMINE SALT IS FOUND ON THE FOU	OLLOWING REGULATORY LISTS
Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	GESAMP/EHS Composite List - GESAMP Hazard Profiles
Australia Inventory of Chemical Substances (AICS)	International Air Transport Association (IATA) Dangerous Goods Regulations
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	International Maritime Dangerous Goods Requirements (IMDG Code)
Schedule 5	United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

National Inventory Status

National Inventory	Status	
Australia - AICS	Yes	
Canada - DSL	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Canada - NDSL	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
China - IECSC	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Europe - EINEC / ELINCS / NLP	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Japan - ENCS	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Korea - KECI	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
New Zealand - NZIoC	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Philippines - PICCS	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
USA - TSCA	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Taiwan - TCSI	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Mexico - INSQ	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Vietnam - NCI	Yes	
Russia - ARIPS	No (2,4-dichlorophenoxyacetic acid isopropylamine salt)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)	

SECTION 16 OTHER INFORMATION

Revision Date	01/11/2019
Initial Date	24/09/2018

SDS Version Summary

Version	Issue Date	Sections Updated
2.1.1.1	24/09/2018	Classification
3.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit₀ IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.